



Dimensions in mm

Tsubaki Chain No.	Pitch	Roller Diameter	Inner Width	
	p			d1
RS06B-LM-NEP-1	9.525	3/8"	6.35	5.72
RS08B-LM-NEP-1	12.70	1/2"	8.51	7.75
RS10B-LM-NEP-1	15.875	5/8"	10.16	9.65
RS12B-LM-NEP-1	19.05	3/4"	12.07	11.68
RS16B-LM-NEP-1	25.40	1"	15.88	17.02
RS20B-LM-NEP-1	31.75	1 1/4"	19.05	19.56
RS24B-LM-NEP-1	38.10	1 1/2"	25.40	25.40

Dimensions in mm

Tsubaki Chain No.	Pin		Link Plate				
	Diameter	Length	Length	Length	Thickness	Thickness	Height
	d2	L1	L2	L	T	t	H (max.)
RS06B-LM-NEP-1	3.28	6.10	7.70	15.10	1.30	1.00	8.20
RS08B-LM-NEP-1	4.45	8.40	10.00	18.60	1.60	1.60	12.00
RS10B-LM-NEP-1	5.08	9.55	11.25	20.80	1.50	1.50	14.70
RS12B-LM-NEP-1	5.72	11.10	13.00	24.40	1.80	1.80	16.10
RS16B-LM-NEP-1	8.28	17.75	19.95	39.30	4.00	3.20	21.00
RS20B-LM-NEP-1	10.19	19.90	23.10	46.60	4.40	3.40	26.40
RS24B-LM-NEP-1	14.63	26.65	31.85	61.70	6.00	5.60	33.40

Dimensions in mm

Tsubaki Chain No.	Transverse Pitch	Min. Tensile Strength acc. to ISO 606	Approx. Mass
	pt	kN	kg/m
RS06B-LM-NEP-1	-	8.9	0.39
RS08B-LM-NEP-1	-	17.8	0.70
RS10B-LM-NEP-1	-	22.2	0.95
RS12B-LM-NEP-1	-	28.9	1.25
RS16B-LM-NEP-1	-	60.0	2.70
RS20B-LM-NEP-1	-	95.0	3.85
RS24B-LM-NEP-1	-	160.0	7.45